

GAS METERS BOX

SKU 50855



Data Sheet-

Box with fibreglass door treated anti-UV, frame and structure in AISI 304 stainless steel


Product conforms to UNI 9036:2015

GAS 290 405

Box for gas meters with anti-UV treated fiberglass door, frame and structure in AISI 304 stainless steel sheet; designed for housing gas metering units with volumetric flow rates up to 6 m³/h.

Product features

- metal body in AISI 304 stainless steel sheet and fiberglass door
- excellent mechanical resistance to impact, atmospheric agents and UV rays
- opening and closing of the box through the 1/4 turn lock, with the supplied square profile key
- easy, fast and safe assembly thanks to the folding flap system
- backrest included
- it can be installed on the wall, inside a niche or fixed to a fence, thanks to the components with rounded edges to ensure maximum safety during use of the product



Technical specifications

- MATERIAL: AISI 304 stainless steel sheet
- COLOUR: RAL 7001
- IMPACT RESISTANCE: IK08
- DEGREE OF PROTECTION: IP20
- VENTILATION SECTION: 1100 mm²
- RADIOFREQUENCY ATTENUATION: < 2 dBm
- EXTERNAL DIMENSIONS 560x405x300 mm (HxWxD)
- INTERNAL DIMENSIONS: 520x290 mm (HxW)
- CLOSURE TYPE: 1/4 turn square closure
- VENTILATION: 50% at the bottom and top
- MOUNTING SYSTEM: folding tabs
- POSSIBLE INSTALLATIONS: on the wall, inside a niche or fixed to a fence

| SKU | DESCRIPTION | WEIGHT |
|-------|----------------|---------|
| 50855 | Gas meters box | 6,30 kg |



