

PULITENE

SKU 70790



Data Sheet

Spray cleaner for cleaning of welded polyethylene and polypropylene

Spray cleaner for cleaning welded polyethylene (PE) and polypropylene (PP).

Instructions for use

Thanks to the powerful dispensing valve, a small amount of product is simply sprayed onto the workpiece to dissolve any impurities that could affect the weld. Wait for a few moments for the solvent to evaporate, then weld as usual.

Technical specifications

- ASPECT: colourless liquid
- ODOR: characteristic alcoholic
- RELATIVE DENSITY OF THE LIQUID PHASE: $0,786 \pm 0,05 \text{ g/cm}^3$
- RELATIVE DENSITY OF THE MIXTURE: $0,715 \pm 0,05 \text{ g/cm}^3$
- FLAMMABILITY POINT LIQUID PHASE (c.c): $< 14^\circ\text{C}$
- FLAMMABILITY OF THE PROPELLANT: extremely flammable
- PROPELLANT INFLAMMABILITY $\sim 360^\circ\text{C}$
- FLAMMABILITY LIMITS PROPELLANT: $1,8 \div 9,5\%$
- WATER SOLUBILITY: partial
- LIPOSOLUBILITY: complete
- SPRAY CAN VOLUME: 520 ml
- PRODUCT VOLUME: 400 ml
- SPRAY CAN PRESSURE: 12 bar
- BURST PRESSURE OF THE SPRAY CAN: 15 bar

Ingredients

Isopropyl Alcohol, Petroleum Distillates

SKU	DESCRIPTION	WEIGHT
70790	Pulitene	0,38 kg